

## BACKLIT FILM

CODE	PRODUCT	BASE	INK COMPATIBILITY				SURFACE	BACK SIDE	THICKNESS		WEIGHT (g/m <sup>2</sup> )	WIDTH (INCH)	LENGTH (M)	LENGTH (ft)
			WATER BASED	(ECO) SOLVENT	LATEX	UV			(µm)	(mil)				
<b>SBFM</b>	Backlit Film Matte / 205 µm (8.2 mil)	PET		✓	✓	✓	Matte	N/A	205	8.2	275	36, 42, 54, 60	30, 50	98.4, 164
<b>SBFS</b>	Backlit Film Satin / 205 µm (8.2 mil)	PET		✓	✓	✓	Satin	Matte	205	8.2	275	36, 42, 54, 60	30, 50	98.4, 164
<b>SBFG</b>	Backlit Film Glossy / 205 µm (8.2 mil)	PET		✓	✓	✓	Glossy	Matte	205	8.2	275	36, 42, 54, 60	30, 50	98.4, 164
<b>WBF</b>	Backlit Film Matte / 205 µm (8.2 mil)	PET	✓		✓	✓	Matte	Glossy	205	8.2	275	36, 42, 54, 60	30, 50	98.4, 164
<b>LBFM</b>	Backlit Film Matte / 185 µm (7.4 mil)	PET			✓	✓	Matte	Glossy	185	7.4	255	36, 42, 54, 60	30, 50	98.4, 164

### FEATURE

- Our backlit films have excellent light diffusivity and can express more vivid colors, which are best for lightboxes and backlit signs.
- You can choose according to your needs as we offer both water and solvent-based PET.
- Water resistant (except WBF if printed with water-based ink).

### APPLICATION

- Backlit displays and signage
- Tradeshow displays
- Lightbox graphics
- Window graphics

