

## Features

**Total Thickness** : 205 µm, PET, Calendered PVC




**Surface** : Glossy, Matte, Satin




**Durability** : Indoor Use



## Recommended Applications




- Backlit displays and signage, Tradeshow displays
- Lightbox graphics, Window graphics



WBF Series		PET Film		
		  		
Product	Description	Width (mm)	Length (m)	Type
WBF	Water Based Backlit Film, Matte Surface	914 ~ 1524	30 ~ 50	Ⓟ
WBF-E	Water Based Backlit Film, Matte Surface, Economic type	914 ~ 1524	30 ~ 50	Ⓟ

SBF Series		PET Film		
		  		
Product	Description	Width (mm)	Length (m)	Type
SBFM	Solvent Based Backlit Film, Matte Surface	914 ~ 1524	30 ~ 50	Ⓟ
SBFM-E	Solvent Based Backlit Film, Matte Surface, Economic type	914 ~ 1524	30 ~ 50	Ⓟ
SBFS	Solvent Based Backlit Film, Satin Surface	914 ~ 1524	30 ~ 50	Ⓟ
SBFG	Solvent Based Backlit Film, Glossy Surface	914 ~ 1524	30 ~ 50	Ⓟ

LBFM		PET Film		
		 		
Product	Description	Width (mm)	Length (m)	Type
LBFM	UV & Latex Based Backlit Film, Matte Surface	914 ~ 1524	30 ~ 50	Ⓟ

PSMW		Calendered PVC Film		
		  		
Product	Description	Width (mm)	Length (m)	Type
PSMW	Backlit Vinyl Surface Glossy Milky White	1370	30 ~ 50	Ⓜ Ⓢ

## Type

